

MEDIUM FILTER – Vilacel VBX

PRODUCT DESIGN :

軽量で安定した構造を実現するABSプラスチック製の4Vデザインコンパクトフィルター。

輸送と設置が簡単な一体型ハンドル。

Compact filter with four – V design made of ABS plastic for a light weight, stable construction. Integrated handle for easy transport and installation

PRODUCT DESCRIPTION :

- High air flow capacity up to 4,250 CMH
- High performance fiberglass media
- High dust holding capacity
- Top cost-benefit ratio
- Low pressure drop with mini-pleat media design
- Stable construction and low weight

APPLICATIONS :

すべてのHVACシステムの二次ろ過または一次ろ過。電子工業、製薬、病院および産業としてクリーンルーム設計の二次ろ過として使用します。

Secondary filtration or main filtration for all HVAC system. Using as secondary filtration in clean room design as electronic industry, pharmaceutical, hospital and industry.

PERFORMANCE :

MODEL	EU Class	Filter Class	Dimension	Air Capacity(SC)	Air Capacity(HC)	Final Pressure
	EN 779	ISO 16890	MM.	CMH / Pa	CMH / Pa	Pa
VBX-MII-6122412	M6	ePM10 70%	305 x 610 x 292	1700 / 95	2100 / 110	500
VBX-MII-6242412	M6	ePM10 70%	610 x 610 x 292	3400 / 95	4250 / 110	500
VBX-MII-7122412	F7	ePM2.5 50%	305 x 610 x 292	1700 / 110	2100 / 120	500
VBX-MII-7242412	F7	ePM2.5 50%	610 x 610 x 292	3400 / 110	4250 / 120	500
VBX-MII-8122412	F8	ePM1 60%	305 x 610 x 292	1700 / 125	2100 / 135	500
VBX-MII-8242412	F8	ePM1 60%	610 x 610 x 292	3400 / 125	4250 / 135	500
VBX-MII-9122412	F9	ePM1 85%	305 x 610 x 292	1700 / 145	2100 / 150	500
VBX-MII-9242412	F9	ePM1 85%	610 x 610 x 292	3400 / 145	4250 / 150	500

SPECIFICATION :

Separator material	Hot-melt separator	Recommended final pressure	2.5 to 3 times initial pressure drop
Using temperature	Max. 70°C	Humidity limit	100 % rel. humidity
Regenerable	No	Incinerable	Yes



FILTER CLASS :



FEARURES :



Vilberg
THE ULTIMATE OF AIR FILTERS

100/2 LEABKLONGMON RD, TUB YAO, LADKRABANG, BANGKOK 10520 THAILAND

TEL. (+662)-360-6602, (+6686)-500-3797, (+6687)-054-4416 FAX. (+662)-360-6603

EMAIL : info@filtermatch2002.com , filtermatch2002@hotmail.com WEBSITE : www.filtermatch2002.com



CERTIFY NO. HK03/0251



ISO 14001:2015
NO. HK03/60492



UL Certified
R26298-20181108